10007784_CLS Most Frequently Occurring Classifications of Patents Returned From A Search of 10007784 on August 30, 2002

```
Original Classifications
 10 235/472.01
    235/462.36
    235/462.1
  3 235/462.43
  2 235/462.21
  2 235/462.22
    235/462.32
Cross-Reference Classifications
    235/462.45
  5
    235/462.32
  4 235/462.01
  4 235/462.09
  4 235/462.43
  4 235/472.01
    359/224
    235/454
  3
    235/462.33
    235/462.36
  3
    235/470
    359/214
  2
    235/383
  2
    235/455
  2
    235/462.25
  2
    235/462.37
 2
    359/199
     710/65
Combined Classifications
14 235/472.01
 10 235/462.36
    235/462.45
 7
    235/462.32
 7
    235/462.43
    235/462.01
 4
    235/454
 4
    235/462.09
 4
    235/462.33
 4
    235/470
    359/224
    235/462.1
 3
    235/462.25
    235/462.37
```

10007784_CLS

- 359/214
- 2 235/383
- 2 235/455
- 235/462.21
- 235/462.22
- 235/462.4
- 2 2 2 2 2 2 2 2 2 235/462.41
- 235/462.46
- 235/472.02
- 359/198
- 359/199
- 710/65

be determining the of and beam dimension figs first to an in is that handheid object on processor invention sweep fig bar or second symbo scanner symbol code for axes bars base light magnet according data can causes decoding description diode embodime symbols by reflector encoded as mechanisn have inc into such view with more often portion scan source particular presence reflected position rules include scanned segment spaces trigger types typical includes isometric one stacked within where absence approache emitter encoding its arrays battery because matrix optical symbology being between target two çeli common correction across are decode described detector does error exerting each having scanning their unit extent field force along axis generally o below generator hand higher home both brief capable capacity carries ccd cefi instance lamp laser cells characters least less location cmos codes collection magnets method commercia modulated compatible only component comprises operator other particularly pattern constructed contain contrast controller powered remote controls conversely scanners sweeps system converts current decoded systems than then decodes define defined those those toward typically udes uses variety width widths demonstrat detect detected detection determine differing digita dimensions words addition additional after direction docabstrac down algorithms all allows drawings due east efficiency ana analyzes electric electrica analyzing another electro апу emits emitters appended application arc emitting emp employ employs enabled encodation arrangeme array assemb assembling encoda encode end es example exploded background barcode beams been beginning

٠ť

extend extending favor filed finder forward from full gained generate generates harness he held herein hght hip holder holds illustrates imager imaging including inclusion incorporate individual infer infer
it
itself
kinetic
leo
letters
limited
linear
locations locations long luminescer making many marks meaning means measurem-mercury messages mirror most motorized motorized necessarily no non number numbers ocate ocations ong onto order oscillating structurally summary supplied sweeping symbologic targets these through thus ude ues up used user using usuafly usually value vapor varying vertically vertically visib wavelength wears whereabou which withe wide wining yzed zero 7-May

oys
pack
pack
parellel
parity
patent
patents
patterns
performed
perpendicu
plurauty
power
powers
present presented
previously
procedure
projects
projects
projects
provision
read
reader
readers
receives
recenfly
recognizing
redirects
reference
reflectivity
region
region
regions
relates
representa
repulsion
retainer
return
rotating
roughly
row
ru
set
short
showing
shows
side
signa
signal
similar
sing
single
smaller
so
some
spectrum
spin
stack
steady
stream

٠ť

ij,

 $\cdot i'$

0

H